



S&B V1200

**The recirculation module
for a room air that is low in viruses, germs and bacteria**

TECHNICAL DATA

TECHNICAL DATA			
Air volume			
Air volume flow in m ³ / h operation	1.500 - 2.500	1.500 - 2.500	1.500 - 2.500
Air volume flow in m ³ / h maximum	3.000	3.000	3.000
Sound level			
1.000 m ³ /h	~ 38 dB	~ 40 dB	~ 44 dB
1.400 m ³ /h	~ 42 dB	~ 44 dB	~ 48 dB
1.800 m ³ /h	~ 48 dB	~ 50 dB	~ 54 dB
Electrical values			
Mains connection	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Power consumption max.	0,5 kW	2,0 kW	2,2 kW
Power consumption ø	300 W	by heating power	
Nominal current consumption max.	3,0 A	9,0 A	9,5 A
Dimension			
Length (without packaging)	1.250 mm	1.250 mm	1.250 mm
Width (without packaging)	1.250 mm	1.250 mm	1.250 mm
Height (without packaging)	500 mm	580 mm	580 mm
Filter area G5	2,81 m ²	2,81 m ²	2,81 m ²
Filter area H14	42,72 m ²	42,72 m ²	42,72 m ²
Weight (without packaging)			
without filter	~ 60 kg	~ 70 kg	~ 75 kg
with filter	~ 80 kg	~ 90 kg	~ 95 kg

FURNISHING

	Basic module	Comfort module	with air curtain
Price	5550,00 €* [*]	6680,00 €* [*]	7580,00 €* [*]
G5 pre-filter	●	●	●
H14 particulate filter	●	●	●
Aluminum casing	●	●	●
Touch display	●	●	●
Remote control on / off / brightness	●	●	●
Filter replacement indicator	●	●	●
Air volume adjustment	●	●	●
optical error message	●	●	●
Electric heating module (heating up to 4 K)		●	●
flat LED lighting	○	●	●
Air curtains for cash registers / workplaces			●
Heating / cooling water register		○	○
individual advertising	○	○	○
Fresh air supply	○	○	○
mobile steel frame / wall bracket	○	○	○
CO ² traffic light	○	○	○

* as of 01/2021; plus packaging and shipping

○ extra charge